

New generation output software with 16 bit rendering (a standard item)

High performance RIP software designed to fully enable all advanced features of the JFX plus series



16 bit rendering eliminates tone jump and produces fine colour reproduction. Different images can be freely nested on the RIP. The web update function has been newly added to Rasterlink Pro 5 to easily achieve both software update and profile download.



**Specifications**

Item	Specifications	
	JFX-1631plus	JFX-1615plus
Print head	On-demand Piezo head	
Print resolution	300x600 dpi, 450x600 dpi, 600x600 dpi, 600x1200 dpi, 1200x1200 dpi	
Ink	Type	LH-100 hard UV ink (C/M/Y/K/W/CL) LF-200 flexible UV ink (C/M/Y/K/W)
	Capacity	600 ml ink pack
Maximum print width (W x D)	1,602 x 3,100mm (63.1 x 122")	1,602 x 1,500 mm (63.1 x 59.1")
	With post-curing unit	1,602 x 2,700 mm (63.1 x 106.3")
Print accuracy	Absolute accuracy	± 0.3 mm (0.01 ") or ± 0.3 % from specified print distance
	Repeatability	± 0.2 mm (0.01 ") or ± 0.1 % from specified print distance
Perpendicularity	± 0.5 mm / 500 mm (0.02 / 19.7")	
Media	Size (W x D)	1,644 x 3,194 mm (64.7 x 125.7")
	Thickness	Max. 50 mm (2")
	Weight	Less than 50 kg (110.2 lbs.) (when the media is loaded evenly)
Media table	Air suction by vacuum	
UV unit	Vacuum area	Vertically divided into 4 zones
		Vertically divided into 2 zones
Post-curing unit	Lifetime **	About 10,000 hours
	UV unit	Equipped with fluorescent UV tube lamp *2
	Lifetime **	About 1,000 hours *3
	Power specifications	1-phase : AC 200 - 240V, 50/60 Hz (power from main unit)
	Power consumption	Less than 400 VA
Dimensions/ Weight (W x D x H)	1,980 mm x 185 mm x 300 mm / 13 kg	(78 x 7.3 x 11.8" / 28.7 lbs.)
	USB 2.0	
Interface	USB 2.0	
Applicable standard	VCCI class A, CE Marking, CB Report, UL, RoHS Directive	
Power specifications	AC 200 - 240 V, 50 / 60 Hz	
Power consumption	Less than 2.0 kVA	
Operational environment	Temperature	15 - 30 °C (59 - 86 °F)
	Humidity	35 - 65 % Rh
	Temperature accuracy	18 - 25 °C (64 - 77 °F)
	Temperature gradient	Less than ± 10 °C / h (18 °F)
	Dust	Equivalent to normal office level
Dimensions (W x D x H)	4,200 x 4,300 x 1,600 mm (165.4 x 169.3 x 63")	4,200 x 2,620 x 1,600 mm (165.4 x 103.1 x 63")
	Weight	1,613 kg (3,556 lbs.)

\*1 Reference value. There is no guarantee as to the lifetime.

\*2 Post-curing unit is equipped with 3 fluorescent UV tube lamps in one set.

\*3 After about 1,000 hours of usage, illumination level declines by about 20%.

**Inks and substrates:**

Please note that properties and adhesion, weather resistance etc. of ink and substrates can vary. Therefore please test materials before printing.  
Some substrates require primer before printing. Please test materials beforehand or ask your sales representative.

**Safety notice:**

You are dealing with UV light sources that may harm your health.

Please follow below guidelines strictly:

- Do not look directly into the UV light source nor place your hand, or expose your skin directly to the UV light source.
- Depending upon print mode, there might occur some VOC emission from printed parts not yet cured and hardened
- In addition, please read the instructions and guidelines of the manual carefully and follow those.

Some of the samples in this folder are artificial renderings • Specifications are subject to change without notice • All trademarks or registered trademarks are the property of their respective owners • Inkjet printers print using extreme fine dots, so colours may vary after replacement of the printing heads, also note that if using multiple printer units, colours could vary slightly from one unit to other unit due to slight individual differences • Composer's errors reserved

MIMAKI EUROPE B.V.

Stammerdijk 7E 1112 AA  
Diemen, The Netherlands  
Tel: +31-20-4627-642

info@mimakieurope.com www.mimakieurope.com

**Supplies**

Item	Colour	Item No.	Remarks
LF-200 Flexible UV Ink	Cyan	SPC-0591C	600 ml ink pack
	Magenta	SPC-0591M	
	Yellow	SPC-0591Y	
	Black	SPC-0591K	
	White	SPC-0591W	
LH-100 Hard UV Ink	Cyan	SPC-0597C	600 ml ink pack
	Magenta	SPC-0597M	
	Yellow	SPC-0597Y	
	Black	SPC-0597K	
	White	SPC-0597W	
	Clear	SPC-0597CL	
Eco-cartridge		OPT-J0237	8 pcs
Cleaning solution (for LF-200 and LH-100)		SPC-0606FS	400 ml cartridge
UV primer GM-1		SPC-0541	500 ml
Fluorescent UV tube lamp		SPC-0690	3 pcs

**Option**

Item	Item No.	Remarks
RU-160 roll unit	OPT-J0252	Delivery & Retraction unit
Ionizer kit	OPT-J0213	1 kit for each unit
Vacuum unit (1 φ - 200)	OPT-J0217	1-phase: 200-240 V, 30 A, 1.9 kW
IF unit for external vacuum	OPT-J0202	1-phase/3-phase: 200-400V, 30A

- A vacuum unit is not included in JFX-1631plus or JFX-1615plus. Please purchase separately.
- Additional power source is required in order to use the vacuum unit.
- Each vacuum unit includes IF units for external vacuum (OPT-J0202).

**Specifications for RU-160 roll unit**

Item	Specifications	
Carrier system	Page to page*	
Usable media	Width	300 mm - 1,600 mm (11.8 - 63")
	Thickness	0.05 mm - 1.0 mm (0.002 - 0.04")
	Weight	Less than 50 kg
	Roll outside diameter	Up to φ 200 mm (7.9")
	Roll inside diameter	3 inch
Print surface	Inside / outside selectable	
Power specifications	1-phase: AC 200-240V, 50/60 Hz, (power from main unit)	
Power consumption	Less than 150 VA	
Dimensions	Incl. JFX-1631plus (W x D x H)	4,300 x 5,000 x 1,600 mm (Main + roll unit) (169.3 x 196.9 x 63")
	Incl. JFX-1615plus (W x D x H)	4,300 x 3,500 x 1,600 mm (Main + roll unit) (169.3 x 137.8 x 63")
Weight	Incl. JFX-1631plus	1,813 kg (Main 1,613 kg + Roll unit 200 kg)
	Incl. JFX-1615plus	1,513 kg (Main 1,313 kg + Roll unit 200 kg)

\* Each print size is limited to the maximum print area available on the flatbed.



Our factory is certified ISO14001:2004  
Mimaki Engineering CO., LTD.

**JFX plus Series**

**Mimaki**



**Highest Precision UV LED Printer**

UV LED CURABLE

23.6 m<sup>2</sup>/h  
MAX. PRINT SPEED

FLEXIBLE / HARD INK

5 CM  
MAX. MEDIA THICKNESS

1200 DPI  
MAX. RESOLUTION

4 COLOURS +  
WHITE & CLEAR AVAILABLE

OPTIONAL ROLL UNIT

UV LED BENEFITS

**plus HIGHER SPEED**

**plus MORE FLEXIBILITY**



JFX-1631plus



JFX-1615plus

MARKET

SIGN GRAPHICS

INDUSTRIAL PRODUCTS

# Experience the great benefits of UV LED printing combined with a dramatic increase in productivity.

Always striving for the best, Mimaki has achieved significant productivity enhancements for its flatbed UV LED printer series JFX with up to 80% higher speeds. The new JFX plus series features a standard post-curing unit that enables printing of up to 23.6 sqm/h. This is nearly twice as fast as previous models.

A roll unit has been developed to boost efficiency and productivity when printing on roll fed substrates.

In addition, Mimaki's IMS\* technology ensures the highest image quality exceeding your customers' expectations.

\* IMS = Intelligent Microstepping System



High speed

High accuracy


Ink variation

Hybrid

Ecology


## Post-curing unit

As standard, JFX plus series is equipped with a post-curing unit that cures the print after its first exposure by UV LEDs thus enabling nearly double the print speed as previous models. Print service providers can now cater to their clients' needs for fast turnarounds, quick changes and short run orders while at the same time increasing productivity and efficiency.




## IMS for highly detailed and accurate prints

The new head positioning mechanism uses high resolution linear scale for fine step accuracy of dot placement. This results in far fewer banding artifacts and even the possibility to print legible 3pt characters.



## High resolution of 1200 x 1200 dpi and variable drops

High image quality is achieved by utilising a resolution of up to 1200 x 1200 dpi and variable dot sizes. Even printing in 4-colour mode realises a non-grainy print, thus prints show smooth gradations and highly detailed images.




## Different UV inks cater to your requirements

Type	LH-100 Hard UV ink	LF-200 Flexible UV ink
Colors	C M Y K + (W) + (CL)	C M Y K + (W)
Features	High scratch and chemical resistance, superior coloration.	200% elasticity, suitable for embossing and other post-processing tasks.
Main Applications	Flat surfaces, acrylic and aluminum compound boards, styrene boards, CCNB etc.	Flat and uneven surfaces, vehicle wraps, vinyl chloride film, packaging, banners etc.

\* As Ink expansion of LF-200 ink varies according to the substrate, please verify your substrate in advance.

## More vivid images with white ink

White ink underprint prevents the transmission of light, resulting in more vivid images.



\* Sample print on transparent acrylic

## Clear ink adds more value to your prints

Glossy or matte finishing varnish with clear ink\* realises astounding and eye-catching effects on your prints. Depending on your design, you can add protective coating to protect surfaces or spot coating for design accents.

\* Clear ink can only be used with LH-100 ink


## Haptic effects with multi-layered print

By printing several layers of ink and/or gloss, your images will not only look more enticing but also will have a haptic feel that will satisfy your clients.

## Print on rigid boards and roll media with the same machine

While printing on rigid substrates up to 50 mm thickness is standard, JFX plus also answers the demand of print service providers for hybrid printing on roll media. An optional roll unit is available, which enhances productivity and efficiency by accommodating unattended printing of several or different jobs\* enabling fast turnaround times.

\* Each job is limited by the max. print size of JFX plus.




## Environmentally friendly printing

Almost no VOCs are generated by UV curing print. In addition, diodes that are used for Mimaki's UV LED system feature a long lifetime and are using considerably less power than conventional UV lamps. Furthermore, by using Mimaki's Eco-cartridge system, waste is reduced as the ink pack inside of the cartridge casing needs to be replaced.

\* The post-curing unit employs a fluorescent UV tube lamp.



## Post-curing unit



## Print & Cut

Add even more productivity and value to your shop with Print & Cut solutions

Raise your efficiency even more by combining JFX plus series printers with Mimaki's CF3 series of cutting plotters enabling highly accurate cuts of all your printed projects. A great way to expand your business to new markets.

